

REXOIL DIAMOND PRO FE

0W-20 SN/CF

REXOIL DIAMOND PRO FE OW-20 SN/CF is an advanced fully synthetic engine oil designed to help provide outstanding engine protection and better fuel economy. It is formulated with a special blend of high performance synthetic base oils supported by a precisely balanced additive system. It is fully compatible with the latest diesel particulate filters (DPFs) and catalytic converters (CATs) found in gasoline vehicles. Thanks to its low-ash additives, it provides superior protection and longer oil change intervals in exhaust systems and engines.

Properties

0 。

- It has low sulfur and phosphorus content.
- Active to clean your engine at the maximum level against harmful soot and impurities.
- It has cleaning feature.
- Thanks to its synthetic structure, the volatility of the oil is low. This provides a decrease in oil reduction.
- It provides fuel economy with its excellent viscosity control feature.
- It provides additional protection against wear by binding to the engine surfaces with the smart molecules it contains.
- creates a layer.
- It facilitates working in the cold with its low temperature fluidity.
- High resistance to tearing due to its high viscosity index.

Approvals and Specifications

- API SN / API SM / API SL
- API CF
- ACEA C3-16 (2016) / C3-12 (2012)
- ACEA C2-16 (2016) / C2-12 (2012)
- ACEA C5-16 (2016)

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.

Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78 www.rexoil.com.tr



- BMW Longlife-04
- MB 229.52/229.51/229.31
- Volkswagen VW50700/Volkswagen VW50400
- Porsche C30
- GM Dexos 2
- Renault RN0700/0710
- Jaguar Land Rover ST JLR.03.5004
- FIAT 9.55535-S3

Technical Specifications

8

Test	Method	Typical Properties
Appearance	Visual	Clear-Bright
Kinematic Viscosity (100°C), [cSt]	ASTM D445	5,6 – 9,3
Viscosity Index	ASTM D2270	Min. 155
Flash Point, °C	ASTM D92	Min. 200
Pour Point, °C	ASTM D97	Max36
Total Base Number, mg KOH/g	ASTM D 2896	Min. 7,0

0

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.

Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78 www.rexoil.com.tr