

## REXOIL

### SHINE OIL

**REXOIL SHINE OILS** are white process oils which have paraffinic structure, formulated with high quality products for wide range of applications. **REXOIL SHINE OILS** have very good color and oxidation stability. Also have a wide range of viscosities for different purpose usage.

#### **Area of Use;**

Plastic, rubber, chemical, agriculture, paper, textile industry, in particular skin oil, wax, ink and paint manufacturing, foam cutting, and also are used as raw materials in industrial lubricants.

#### **Technical Properties**

Test	Method	Typical Properties			
		S-2	S-4	S-6	S-8
Kinematic Viscosity (40°C) [cSt]	ASTM D445	7,2 – 8,7	19,3 – 24,2	28,8 – 35,2	41,4 – 55,6
Kinematic Viscosity (100°C) [cSt]	ASTM D445	1,8 – 2,6	3,8 – 4,8	5,6 – 6,9	7,0 – 7,9
Viscosity Index	ASTM D2270	Min. 110	Min. 120	Min. 120	Min. 120
Flash Point, °C	ASTM D92	Min.150	Min.200	Min. 210	Min. 220
Pour Point, °C	ASTM D97	Max. -15	Max. -15	Max. -15	Max. -15
Color (ASTM)	ASTM D1500	L0,5	L0,5	L0,5	L0,5
Color (Saybolt)	ASTM D156	+30	+30	+30	+30
<b>Carbon Distribution</b>					
% Aromatic	ASTM D3238	0,0	0,0	0,0	0,0
% Naphanic	ASTM D3238	20,9	17,7	17,2	21,5
% Paraffinic	ASTM D3238	79,1	82,3	82,8	78,5