

PRODUCT DATA SHEET



REXOIL

CHROME LPG

10W-40 SL/CF

REXOIL CHROME LPG 10W-40 is semi-synthetic motor oil which blended with synthetic base oils and high quality additives specifically to meet the needs of the LPG and gasoline engines. It is used safely in all vehicles that work by gasoline and LPG. It's also are recommended for use in engines of small commercial vehicles, light trucks and vans.

Properties

- Effective detergent and dispersant additives prevent deposit formation and keeps engine clean.
- Provides fuel economy by excellent viscosity control property.
- It forms extra protection layer against to abrasion by bonding to surface of engines with smart molecules that contains.
- It makes easy to work at cold weather by its viscosity.

Approvals and Specifications

- API SL/CF
- ACEA A3/B3-04
- MB Approval 229.1

- VW 501.01 / 505.00
- ACEA A3/B4-04
- AVTOVAZ LADA cars

Technical Specifications

| Test | Method | Typical Properties |
|------------------------------------|------------|--------------------|
| Kinematic Viscosity (100°C), [cSt] | ASTM D445 | 12,5 - 16,3 |
| Viscosity Index | ASTM D2270 | Min. 145 |
| Flash Point, °C | ASTM D92 | Min. 220 |
| Pour Point, °C | ASTM D97 | Max30 |