



Motor Oil & Lubricants

## REXOIL PLATINUM EXTRA

### 15W-40 CI-4/SL

**REXOIL PLATINUM EXTRA 15W-40** is super high performance (SHPD) diesel engine oil which has been developed for use in next-generation heavy duty diesel engines can be safely used four seasons. It is formulated with high quality base and full synthetic base oil (Group II, Group III) by adding superior performance additives. It is recommended for use in heavy duty vehicles and construction equipment of diesel engines with or without turbocharger.

#### *Properties*

- Provides protection against acidification by the high TBN value.
- Provides easily the first work at low temperatures by its excellent viscosity.
- Advanced additive system keeps engine parts clean by controlling formation of deposit and sludge.
- Excellent viscosity control features provides fuel economy and long service life.
- Provides excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion.

#### *Existing OEM Approvals*

- MB-Approval 228.3

#### *Approvals and Specifications*

API CI-4/CH-4/CG-4/CF-4/CF,API SL/SJ,ACEA E7-12 (2012),ACEA A3/B4-12 (2012),MB-Approval 228.3  
MB-Approval 229.1,MAN M 3275,Volvo VDS-3Mack EO-NMack EO-M PLUS,CAT ECF-2,CUMMINS CES  
20076 / 20077/20078,CAT ECF-1-a,Renault Truck RLD-2,Deutz DQC-III-10,Global DHD-1,Detroit Diesel  
DDC 93K215,MTU Type 2



Motor Oil & Lubricants

### Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	12,5 - 16,3
Viscosity Index	ASTM D2270	Min. 130
Flash Point, °C	ASTM D92	Min. 220
Pour Point, °C	ASTM D97	Max. -27
Total Base Number, mg KOH/g	ASTM D2896	Min. 10,0