



Motor Oil & Lubricants

REXOIL DIAMOND PRO F

10W/30 CI-4/SL

REXOIL DIAMOND PRO F 10W/30 is high performance diesel engine oil which is prepared with synthetic base oils and advanced additive packages to provide excellent low temperature fluidity, high temperature viscosity retention, and volatility control. It is recommended for passenger cars and commercial vehicles, European and American design, low-emission, turbocharged engines. It is also recommended for vehicles that are working on roads and high speed / heavy load, light and heavy truck transport over short distances as well as upload / download operating, construction and agricultural land, such as vehicles running under heavy load conditions.

Properties

- Provides excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion.
- Contains intelligent molecules that cling to your engine and form an extra layer that protects from start up.
- Provides easily the first work at low temperatures by its excellent viscosity.
- Extends oil change intervals even at high sulfur fuel use.

Approvals and Specifications

- API CI-4/CH-4/CG-4/CF-4/CF
- ACEA E7-08
- MAN M 3275
- Caterpillar ECF-2
- JASO DHD-1
- Volvo VDS-3
- MTU Level 2
- Deutz DQC-III-05
- API SL/SJ
- ACEA A3/B4-10
- MB-Approval 228.3
- Renault RLD-2
- MACK EO-M Plus
- CUMMINS CES 20076 / 20077/20078
- Detroit Diesel
- Global DHD-1



Motor Oil & Lubricants

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	9,3 - 12,5
Viscosity Index	ASTM D2270	Min. 145
Flash Point, °C	ASTM D92	Min. 210
Pour Point, °C	ASTM D97	Max. -33
Total Base Number, mg KOH/g	ASTM D 2896	Min. 10,0

