



Motor Oil & Lubricants

REXOIL

ALESTA ML SERIES

REXOIL ALESTA ML SERIES are premium quality cylinder lubricants designed for use in all slow speed two stroke crosshead diesel engines which burn residual fuel with sulphur content between %2,5-%4,0 weight.

Properties

- Has excellent deposit control and minimizes deposit build up on piston, piston rings, under piston spaces and cylinder parts.
- Have outstanding acid neutralizing properties which help to prolong the life of components.
- It is suitable for engines which work by heavy fuels with high sulfur content.

Technical Properties

Test	Method	Typical Properties				
SAE Grade / TBN		50/25	50/40	50/50	50/70	50/100
Kinematic Viscosity (100°C), [cSt]	ASTM D445	17,5 – 21,9	17,5 – 21,9	17,5 – 21,9	17,5 – 21,9	17,5 – 21,9
Total Base Number, mg KOH/g	ASTM D 2896	22,5 – 28,5	37,0 – 42,5	47,0 – 52,5	67,0 – 72,5	90 - 110
Viscosity Index	ASTM D2270	Min. 90	Min. 90	Min. 90	Min. 90	Min. 90
Flash Point, °C	ASTM D92	Min. 240	Min. 240	Min. 240	Min. 240	Min. 240
Pour Point, °C	ASTM D97	Max. -12	Max. -12	Max. -10	Max. -10	Max. -10