



Motor Oil & Lubricants

REXOIL

ALESTA S SERIES

REXOIL ALESTA S SERIES, designed with quality base oils and new technology additives for the lubrication of the high and medium speed trunk piston marine diesel engines.

Properties

- Shows good oil film strength at extreme pressures.
- Reduced deposits in piston ring belt and cylinder liners
- Provides superior resistance to water.
- Extended diesel engine life through reduced risk of ring sticking and breakage.

Technical Properties

Test	Method	Typical Properties					
SAE Grade / TBN		30/12	40/12	30/15	40/15	30/20	40/20
Kinematic Viscosity (100°C), [cSt]	ASTM D445	9,3 – 12,5	12,5 – 16,3	9,3 – 12,5	12,5 – 16,3	9,3 – 12,5	12,5 – 16,3
Total Base Number, mg KOH/g	ASTM D 2896	11,2 – 13,2	11,2 – 13,2	13,5 – 17,5	13,5 – 17,5	18,2 – 22,3	18,2 – 22,3
Viscosity Index	ASTM D2270	Min. 90	Min. 90	Min. 90	Min. 90	Min. 90	Min. 90
Flash Point, °C	ASTM D92	Min. 220	Min. 230	Min. 220	Min. 220	Min. 230	Min. 230
Pour Point, °C	ASTM D97	Max. -15	Max. -15	Max. -15	Max. -15	Max. -15	Max. -15