

REXOIL

ALESTA H SERIES

REXOIL ALESTA H SERIES are trunk piston engine oils which are designed for the lubrication of medium speed diesel engines when a superior detergency property is required. They are suitable for use with engines burning residual fuel oils between %2,5-%4,0 sulphur and removes the need for ship operators to carry two lubricant types to cover both low and high sulphur fuels.

Properties

- Excellent resistance to the negative effects of contamination with residual fuel.
- Offers acid neutralizing properties which help to prolong the life of competent.
- Excellent thermal resistance and high temperature oxidation resistance.
- Ensures outstanding cleanliness of the hot and cold parts of the engine, due to improved detergent and dispersant properties.

Technical Properties

Test	Method	Typical Properties			
SAE Grade / TBN		30/40	40/40	30/55	40/55
Kinematic Viscosity (100°C), [cSt]	ASTM D445	9,3 - 12,5	12,5 - 16,3	9,3 - 12,5	12,5 - 16,3
Total Base Number, mg KOH/g	ASTM D 2896	37,5 - 42,5	37,5 - 42,5	50,5 - 60,0	50,5 - 60,0
Viscosity Index	ASTM D2270	Min. 90	Min. 90	Min. 90	Min. 90
Flash Point, °C	ASTM D92	Min. 230	Min. 230	Min. 230	Min. 230
Pour Point, °C	ASTM D97	Max. -18	Max. -15	Max. -15	Max. -15