



Motor Oil & Lubricants

TRACTOR FLUID 422

UTTO & STOU

TRACTOR FLUID 422 is multi-purpose universal tractor transmission oil (UTTO) which is crafted with highly refined mineral base oils and additive packages. It can be used for agricultural and construction machines power transmission units, oil-bath brakes, hydraulics, gears, axles and other transmission systems. It shows very good performance in powertrain of moving equipment, drive axles, clutches and the PTO& hydraulic systems.

High performance **TRACTOR FLUID 422** oil is suitable to use for diesel / gasoline engines (STOU).

Properties

- It is economic due to have wide use ranges.
- It has excellent low temperature and high temperature performance.
- Includes regulatory friction additives so brake system works quiet and high efficiency.
- Due to the high thermal and oxidation stability, it increases the work efficiency by preventing the formation of deposits.

Approvals and Specifications

UTTO

- API GL-4
- John Deere J20C
- Case New Holland MAT 3525 and 3526
- ZF TE-ML 07B, 06D, 06C, 06B
- **SAE 80W**
- Massey Ferguson CMS M1143 and 1135
- Allison C4
- Ford M2C 134D

STOU

- API CF-4, API SF
- Massey Ferguson CMS M1144 and 1139
- John Deere J27
- New Holland NH 03D/C and NH 024C
- **SAE 10W30**
- ACEA E2/E3
- MB-Approval 228.3
- Ford M2C 159B/C



Motor Oil & Lubricants

TRACTOR FLUID 422

UTTO & STOU

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	9,5 – 12,5
Density @ 15 °C	ASTM 4052	0,865 – 0,885
Viscosity Index	ASTM D2270	Min. 140
Flash Point, °C	ASTM D92	Min. 210
Pour Point, °C	ASTM D97	Max. -30