

REXOIL MOTORCYCLE

4T 20W-50

REXOIL MOTORCYCLE 4T 20W-50 combine highly refined quality mineral oils and advanced additives to provide good engine cleanliness, good wear protection and corrosion protection. It's suitable all seasons for air cooled/liquid-cooled 4-stroke engines and wet clutches.

Properties

- Provides year round engine protection and high performance.
- Helps to keep engines clean for smoother operation.
- Provides fuel economy by excellent viscosity control property.
- Shear stable viscosity improvers help resist oil film breakdown.

Approvals and Specifications

API SJ

JASO MA (T903:2011)

JASO MA2 (T903:2011)

Technical Properties

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	16,3 - 21,9
Viscosity Index	ASTM D2270	Min. 115
Flash Point, °C	ASTM D92	Min. 230
Pour Point, °C	ASTM D97	Max24

Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78 www.rexoil.com.tr





REKSOIL PETROKİMYA SAN. VE TİC. A.Ş. Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78 www.rexoil.com.tr