



Motor Oil & Lubricants

## REXOIL

### TRANSMISSION 85W/140 GL-5

**REXOIL TRANSMISSION 85W/140** is a high-performance gear lubricant formulated from select base oils and an advanced additive system. Thanks to its special formula provides effective protection against corrosion may occur in severe operating conditions. Suitable for differentials and transaxles of vans, trucks, and buses when the manufacturer recommends a GL-5 transmission oil with a viscosity of SAE 85W-140.

#### Properties

- Shows very high extreme-pressure properties for optimal protection against scuffing.
- Increased protection against wear and tear, also under high stress working conditions.
- Have extreme pressure (EP) resistant to corrosion and oxidation and antifoaming properties.
- It is suitable in four seasons due to its multigrade properties.

#### Approvals and Specifications

- API GL-5/GL-4
- MAN 342M-1, MAN 342 M-2
- Volvo 1273.12
- U.S. Steel 224
- ZF TE-ML 05A, 7A, 12E, 16B, C and D, 17B, 19B, 21B
- Scania STO 1:0
- DIN 51517 Part 3
- AGMA 9005-D94

#### Technical Properties

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	Min. 24,8
Viscosity Index	ASTM D2270	Min. 93
Flash Point, °C	ASTM D92	Min. 240
Pour Point, °C	ASTM D97	Max. -15