

REXOIL

TRANSMISSION

80W/90 GL-4

REXOIL TRANSMISSION 80W/90 is special gear oil which is formulated with superior additives and mineral base oils derived from modern refining. Have been developed to be used in gearboxes of cars and commercial vehicles.

Properties

- Maintains film strength for effective lubrication.
- Increased protection against wear and tear, also under high stress working conditions
- Promote efficient gear operation by balancing low and high temperature viscosity
- Protect gears from deposit buildup under the stress caused by hauling extra-heavy loads with our thermally durable additive system, which resists oxidation and deposits
- Have extreme pressure (EP) resistant to corrosion and oxidation and antifoaming properties.

Approvals and Specifications

- API GL-4
- U.S. Steel 224
- AGMA 9005-D94

- David Brown S1.53.101(E)
- DIN 51517 Part 3
- ZF TE-ML 02A, 08, 16A, 17A, 19A

Technical Properties

| Test | Method | Typical Properties |
|------------------------------------|------------|--------------------|
| Kinematic Viscosity (100°C), [cSt] | ASTM D445 | 14,5 – 18,5 |
| Viscosity Index | ASTM D2270 | Min. 95 |
| Flash Point, °C | ASTM D92 | Min. 220 |
| Pour Point, °C | ASTM D97 | Max20 |