



Motor Oil & Lubricants

MOTO

4T 10W/40 SL

MOTO 4T 10W/40 is synthetic 4-stroke motorcycle oil which blended with synthetic base oils and high quality additives for four-cycle, air- or water-cooled motorcycles. This oil is wet-clutch compatible and recommended for motorcycles where an API SL or JASO MA/MA2 fluids are specified.

Properties

- Reduces internal engine friction even under the most arduous riding conditions.
- Optimized for lubrication systems where engine, gearbox and clutch are integrated (wet sump).
- Provides excellent engine performance in air and water cooled engines even at high temperatures.
- Due to its high viscosity index property, creates homogenous film layer and prevents clutch slippage and premature disk wear.
- Provides fuel economy by excellent viscosity control property.
- Have excellent low-temperature flow characteristics can help minimize engine wear during startup.

Approvals and Specifications

- API SL
- JASO MA2 (T903:2011)
- JASO MB (T903:2011)
- JASO MA (T903:2011)

Technical Properties

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	12,5 - 16,3
Viscosity Index	ASTM D2270	Min. 145
Flash Point, °C	ASTM D92	Min. 210
Pour Point, °C	ASTM D97	Max. -30