TITANIUM POWER

SAE 50 CF/SF

REXOIL TITANIUM POWER SAE 50 is a premium quality monograde engine oil formulated with refined mineral base oils and a carefully balanced additive package. Specially developed for older generation diesel and gasoline engines, it delivers reliable performance in hot climates and under high-load operating conditions. Its high viscosity ensures a strong and durable oil film, providing excellent wear protection where multigrade oils are not required or recommended. The product is particularly suitable for naturally aspirated or lightly turbocharged diesel engines, heavy-duty trucks, buses, off-road equipment, stationary engines.

Features and Benefits

- Strong and stable oil film minimizes wear in high-load and high-temperature conditions.
- Low volatility base oils reduce oil burn-off and topping-up frequency.
- Advanced detergency and dispersancy provide effective sludge and varnish control in both diesel and gasoline engines.
- Resists thickening and deposit formation at elevated temperatures.
- Formulated to protect against leaks and ensure compatibility with standard engine seals.

Approval and Specifications

API CF/SF; MAN 270; MB 228.0; MTU TYPE 1

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	17,0 – 21,5
Density @ 15^{0}C g/ml	ASTM D4052	0,880 - 0,905
Viscosity Index	ASTM D2270	Min. 90
Flash Point, °C	ASTM D92	Min. 240
Pour Point, °C	ASTM D97	Max. -15
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,0

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr