# TITANIUM POWER

## *SAE 40 CF/SF*

**REXOIL TITANIUM POWER SAE 40** is a monograde engine oil which is formulated with high-quality refined base oils and advanced additives. It is suitable cars, public work buses and mixed fleets trucks where two and four-stroke diesel and gasoline engines requiring SAE 40 viscosity. It is also recommended for use in engines in construction equipment, agricultural machinery, marine and other off-road applications.

### *Features and Benefits*

- Stable viscosity maintains a durable oil layer for long-lasting protection in engines where multigrade oils are not required.
- Provides enhanced wear and corrosion protection, extending engine life.
- safeguards vital engine components from corrosion caused by fuel combustion by-products.
- Effective detergency and dispersancy help control deposits, varnish, and soot.
- Provides low oil consumption thanks to its low volatility feature.

### *Approval and Specifications*

API CF/SF; MAN 270; MB 228.0; MTU TYPE 1

### *Technical Specifications*

| Test | Method | Typical Properties |
|---|---|---|
| **Kinematic Viscosity (100°C), [cSt]** | ASTM D445 | 13,5 – 16,0 |
| **Density @ 15$^0$C g/ml** | ASTM D4052 | 0,880 - 0,905 |
| **Viscosity Index** | ASTM D2270 | Min. 90 |
| **Flash Point, °C** | ASTM D92 | Min. 240 |
| **Pour Point, °C** | ASTM D97 | Max. -15 |
| **Total Base Number, mg KOH/g** | ASTM D2896 | Min. 7,0 |

### *Health and Safety*

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

### *Storage & Handling*

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

**REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.**
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr