TITANIUM POWER

SAE 30 CF/SF

REXOIL TITANIUM POWER SAE 30 is a premium quality monograde engine oil engineered with high quality solvent-refined mineral base oils and a carefully balanced additive package. It is specially formulated for older, naturally aspirated or lightly turbocharged diesel engines and gasoline engines operating in hot climates or high-load conditions. It provides a strong oil film, ensuring durable protection in engines where multigrade oils are not required or recommended.

Features and Benefits

- Reduced oil consumption and improved film strength.
- Provides excellent wear protection for engine components under high-load conditions.
- Effective sludge and varnish control in both gasoline and diesel engines.
- Provides low oil consumption thanks to its low volatility feature.

Approval and Specifications

API CF/SF; MAN 270; MB 228.0; MTU TYPE 1

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	10,0 – 12,3
Density @ 15^{0}C g/ml	ASTM D4052	0,880 - 0,900
Viscosity Index	ASTM D2270	Min. 90
Flash Point, °C	ASTM D92	Min. 240
Pour Point, °C	ASTM D97	Max. -15
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,0

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr