TITANIUM SAE 50

API CC/SC

REXOIL TITANIUM SAE 50 is a monograde engine oil formulated with high-quality mineral base oils and selected additives to provide effective protection for older generation diesel and gasoline engines operating under moderate conditions. It is designed for use in older generation naturally aspirated diesel and gasoline engines operating under moderate service conditions. It offers excellent engine cleanliness, wear protection, and oxidation stability, ensuring reliable engine performance and extended engine life.

This oil meets the requirements of both diesel (API CC) and gasoline (API SC) service categories, making it a versatile solution for mixed fleets or single-grade engine applications.

Features and Benefits

- Reduces engine wear and extends engine life.
- Provides enhanced wear and corrosion protection, extending engine life.
- Have wide usage applications.
- Have good oxidation stability and detergent performance.

Approval and Specifications

API CC/SC

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	17,0 – 21,5
Density @ 15^{0}C g/ml	ASTM D4052	0,885 - 0,910
Viscosity Index	ASTM D2270	Min. 90
Flash Point, °C	ASTM D92	Min. 240
Pour Point, °C	ASTM D97	Max. -10

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr