TITANIUM SAE 40

API CC/SC

REXOIL TITANIUM SAE 40 is reliable quality monograde engine oil formulated with selected mineral base oils and a balanced additive package. It is designed for older generation diesel and gasoline engines requiring API CC or SC performance levels.

The product ensures stable lubrication in moderate to high ambient temperatures and provides reliable protection for engines where multigrade oils are not required or recommended. It is suitable for use in naturally aspirated diesel engines, gasoline engines, light-duty trucks, buses, tractors, agricultural machinery, construction equipment, stationary engines, and other off-road applications operating under normal service conditions.

Features and Benefits

- Maintains oil film strength to protect moving parts under load.
- Resists oil thickening and deposit formation at elevated operating temperatures.
- Safeguards engine components against rust and corrosive by-products.
- Helps protect against oil leaks and maintains compatibility with standard seals.
- Provides sludge and deposit control in older diesel and gasoline engines.

Approval and Specifications

API CC/SC

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	13,0 – 16,0
Density @ 15^0C g/ml	ASTM D4052	0,880 - 0,905
Viscosity Index	ASTM D2270	Min. 90
Flash Point, °C	ASTM D92	Min. 240
Pour Point, °C	ASTM D97	Max. -10

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr