TITANIUM SAE 30

API CC/SC

REXOIL TITANIUM SAE 30 is a high-quality monograde mineral engine oil designed to deliver dependable lubrication for engines built to earlier generation standards. It is formulated with carefully refined base oils and a proven additive package that helps protect against wear and deposits. Recommended for use in older gasoline engines requiring API SC and light-duty diesel engines requiring API CC, operating in warmer climates or under continuous load. Typical applications include passenger cars, tractors, light trucks, and stationary engines where an SAE 30 grade is specified.

Features and Benefits

- Prevents oil passages and filters from clogging, ensuring steady oil flow.
- Minimizes formation of varnish, resin, and carbon layers on hot surfaces.
- Keeps internal surfaces cleaner, supporting more efficient combustion and lower emissions.
- Maintains consistent lubrication performance throughout the oil drain interval.
- Minimizes piston and ring wear, extending engine life.
- Provides protection against rust and corrosion during operation and storage.
- Good oxidation and thermal stability under elevated temperatures.
- Compatible with seals and gaskets typically used in older engine designs.

Approval and Specifications

API CC/SC

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	9,5 – 12,3
Density @ 15^{0}C g/ml	ASTM D4052	0,880 - 0,905
Viscosity Index	ASTM D2270	Min. 90
Flash Point, °C	ASTM D92	Min. 240
Pour Point, °C	ASTM D97	Max. -10

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr