TITANIUM SAE 10W

API CC/SC

REXOIL TITANIUM SAE 10W is a monograde mineral engine oil developed with carefully selected base oils and additive systems to ensure reliable lubrication and protection. It is recommended for older gasoline engines (API SC) and light-duty diesel engines (API CC) operating under moderate conditions. Suitable for passenger cars, agricultural tractors, and equipment where SAE 10W grade monograde oils are specified, particularly in temperate climates.

Features and Benefits

- Prevents oil passages and filters from clogging, ensuring steady oil flow.
- Reduces the risk of piston crown deposits and ring sticking, preserving compression.
- Minimizes formation of varnish, resin, and carbon layers on hot surfaces.
- Keeps internal surfaces cleaner, supporting more efficient combustion and lower emissions.
- Maintains consistent lubrication performance throughout the oil drain interval.
- Minimizes piston and ring wear, extending engine life.
- Provides protection against rust and corrosion during operation and storage.

Approval and Specifications

API CC/SC

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	5,2 – 6,8
Density @ 15^{0}C g/ml	ASTM D4052	0,870 - 0,885
Viscosity Index	ASTM D2270	Min. 90
Flash Point, °C	ASTM D92	Min. 220
Pour Point, °C	ASTM D97	Max. -15

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr