TITANIUM POWER

SAE 70 CF/SF

REXOIL TITANIUM POWER SAE 70 is a premium quality, high-viscosity monograde engine oil formulated with carefully selected solvent-refined base oils and an advanced additive package. It is designed to deliver superior lubrication and protection in older generation diesel and gasoline engines operating under severe conditions, high loads, and hot climates.

Its high viscosity ensures the formation of a durable and strong oil film, providing reliable wear protection where multigrade oils are not required or recommended. The product is especially suitable for naturally aspirated and lightly turbocharged diesel engines in heavy-duty trucks, buses, off-road equipment, stationary engines, and mixed fleet applications.

Features and Benefits

- Strong oil film reduces engine wear in high-load and high-temperature operations.
- Resists oil thickening and deposit formation under severe thermal stress.
- Formulated with low volatility base oils to minimize oil burn-off.
- Ensures reliable protection for both diesel and gasoline engines in harsh conditions.

Approval and Specifications

API CF/SF; MAN 270; MB 228.0; MTU TYPE 1

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	26,1 – 29,8
Density @ 15^{0}C g/ml	ASTM D4052	0,890 - 0,925
Viscosity Index	ASTM D2270	Min. 90
Flash Point, °C	ASTM D92	Min. 240
Pour Point, °C	ASTM D97	Max. -10
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,0

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr