TITANIUM SAE 70

API CC/SC

REXOIL TITANIUM SAE 70 is a monograde engine oil formulated from high-quality mineral base oils and carefully selected additives to provide reliable protection for older generation naturally aspirated diesel and gasoline engines. It is recommended for engines requiring API CC or API SC performance levels and is particularly suitable for mixed fleets operating under moderate service conditions. With its stable viscosity, excellent oxidation resistance, and effective control of sludge and deposits, this oil ensures long-lasting engine cleanliness, reduced wear, and dependable performance even at elevated operating temperatures.

Features and Benefits

- Maintains stable oil film at high operating temperatures.
- Provides protection against rust and corrosion.
- Controls sludge and deposit formation, keeping engines clean.
- Reduces wear, extending engine service life.
- Reliable lubrication for engines under moderate service conditions.

Approval and Specifications

API CC/SC

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	26,1 – 29,8
Density @ 15^{0}C g/ml	ASTM D4052	0,890 - 0,920
Viscosity Index	ASTM D2270	Min. 90
Flash Point, °C	ASTM D92	Min. 250
Pour Point, °C	ASTM D97	Max. -6

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr