POWERGEN 20W-40

REXOIL POWERGEN 20W-40 is a high-quality **zinc-free** and **chlorine-free** engine oil developed for use in large stationary gas engines and medium-speed diesel engines operating under severe load and extended drain conditions. It is engineered using premium base oils and a low-ash additive system to ensure excellent piston deposit control, valve protection, and oxidation stability.

This oil is specifically designed to meet the latest requirements of **LMOA Generation 5, GE Jenbacher Generation 4 Long Life, Caterpillar 3600 Series** and **API CF-2** performance standards. It is suitable for continuous-duty engines fueled by natural gas, landfill gas, biogas, or light diesel, commonly used in power generation and industrial environments.

Features and Benefits

- Designed to support long drain intervals in accordance with OEM monitoring (e.g., TAN/TBN, oxidation, nitration thresholds), minimizing maintenance costs.
- Provides excellent anti-wear and cleanliness without metallic or halogenated additives.
- High thermal stability resists viscosity increases and deposits from oxidation and nitration, even in high-temperature or high-load operations.
- Keeps pistons, combustion chambers, and valve decks clean, reducing ring sticking and extending engine uptime.
- Protects against rust, corrosive acids from combustion gases, and liner wear, especially under high-load, continuous operation.

Approval and Specifications

LMOA Generation 5; G.E. Generation 4 Long Life; Caterpillar 3600; API CF-2

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	13,0 – 16,0
Density @ 15^0C g/ml	ASTM D4052	0,880 - 0,890
Viscosity Index	ASTM D2270	Min. 105
Total Base Number, mg KOH/g	ASTM D2896	16,8 – 17,5
Flash Point, °C	ASTM D92	Min. 240
Pour Point, °C	ASTM D97	Max. -26

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr