PLATINUM EXTRA 20W-60

API CI-4/SL, DTFR 15B110 (MB 228.3)

REXOIL PLATINUM EXTRA 20W-60 is a high-performance heavy-duty diesel engine oil formulated with high-quality base oils and advanced additive technology. It is designed to provide reliable protection, durability, and consistent performance for both modern and older diesel engines operating under severe service conditions.

The product delivers excellent engine cleanliness, wear protection, and resistance to oxidation and oil degradation, making it suitable for use in demanding environments and extended service intervals where recommended by OEMs.

It is recommended for heavy-duty diesel engines used in trucks, buses, and construction machinery, including both turbocharged and naturally aspirated engines. It is also suitable for mixed fleet operations requiring API CI-4 / SL performance levels. Its robust formulation ensures reliable operation under high load, high temperature, and harsh working conditions, contributing to extended engine life and improved operational efficiency.

Features and Benefits

- **Excellent Wear Protection:** Reduces engine wear and extends engine life.
- **High Thermal Stability:** Maintains viscosity and performance at high temperatures.
- **Outstanding Detergency & Dispersancy:** Keeps engine components clean and minimizes deposits.
- **Oxidation Resistance:** Prevents oil thickening and sludge formation.
- **Soot Handling Capability:** Effectively controls soot-related wear and deposits.
- **Extended Oil Life:** Supports longer drain intervals (as per OEM recommendations).
- **Corrosion Protection:** Protects engine components against rust and corrosion.
- **Reliable Performance in Harsh Conditions:** Suitable for heavy-duty and severe operations.

Approval and Specifications

API CI-4/CH-4; API SL/SJ; ACEA E7; DTFR 15B110 (MB-Approval 228.3); MAN 3275-1; VOLVO VDS-3; MACK EO-N; Renault Trucks RLD-2/RXD; CUMMINS CES 20078; Detroit Diesel DDC93K215; MTU Type 2; Deutz DQC III 18; Caterpillar ECF-2; JASO DH-1; Global DHD-1

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	22,0 – 26,0
Density @ 15^{0}C g/ml	ASTM D4052	0,880 - 0,905
Viscosity Index	ASTM D2270	Min. 130
Flash Point, °C	ASTM D92	Min. 240
Pour Point, °C	ASTM D97	Max. -20
Total Base Number, mg KOH/g	ASTM D2896	Min. 10,0

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr