DIAMOND SYN 5W-30

API SM/CF

REXOIL DIAMOND SYN 5W-30 is a premium, fully synthetic engine oil engineered to meet the high-performance demands of today's gasoline and diesel engines. Formulated with advanced additive technology, it provides outstanding protection against wear, sludge, and high-temperature deposits, ensuring extended engine life and optimum efficiency under all driving conditions.

This multigrade lubricant offers excellent cold-start performance and maintains stable viscosity at high temperatures, making it perfectly suited for year-round use in both urban and highway driving. Recommended for use in passenger cars and light commercial vehicles requiring performance levels of API SM/CF.

Features and Benefits

- Provides outstanding protection against engine wear, particularly during cold starts and stop-and-go driving.
- Keeps engine components clean by preventing sludge and varnish formation.
- Offers superior thermal and oxidative stability, which extends oil life and maintains performance over time.
- Enhances fuel efficiency thanks to its optimized viscosity profile.
- Supports long drain intervals as per manufacturer recommendations.
- Ensures low oil consumption due to its excellent volatility control.
- Compatible with emission control systems, including catalytic converters.

Approval and Specifications

API SM/CF; ACEA A3/B4; MB. 229.3; VW 502.00/ 505.00; BMW LONGLIFE-98

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	10,3 - 12,3
Density @ 15^{0}C g/ml	ASTM D4052	0,835 - 0,865
Viscosity Index	ASTM D2270	Min. 145
Flash Point, °C	ASTM D92	Min. 220
Pour Point, °C	ASTM D97	Max. -35
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,3

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr