MOTORCYCLE 2T

REXOIL MOTORCYCLE 2T is a two-stroke engine oil designed to meet the demanding performance needs of modern two-stroke motorcycles, scooters, and small engine equipment. Engineered with a low-ash additive system and meets the performance requirements of **API TC, JASO FC, ISO-L-EGC, and TISI** standards, ensuring superior protection, cleanliness, and reliability. It can be safely used in air-cooled and water-cooled 2-stroke motorcycles, scooters, chainsaws, mopeds, lawnmowers, and other 2-stroke engines.

Suitable for **pre-mix or oil-injection systems**. Pre-mix systems (typical ratio **1:50** or as per OEM).

Features and Benefits

- Outstanding lubrication minimizes wear and extends engine life.
- Excellent detergency keeps piston and exhaust ports clean.
- Low smoke emission for cleaner operation and reduced environmental impact.
- Anti-seizure protection for pistons and bearings at high temperatures.
- Good miscibility with fuel, ensuring easy mixing and consistent performance.

Approval and Specifications

API TC; JASO FC; ISO L-EGC; TISI

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	7,2 – 9,5
Density @ 15^{0}C g/ml	ASTM D4052	0,880 - 0,890
Viscosity Index	ASTM D2270	Min. 90
Flash Point, °C	ASTM D92	Min. 230
Pour Point, °C	ASTM D97	Max. -24

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr