OUTBOARD 2T

REXOIL OUTBOARD 2T is a high-performance, ashless two-stroke engine oil specifically formulated to meet the stringent requirements of modern marine outboard engines. Utilizing advanced ashless additive technology and high-quality base oils, this lubricant provides superior protection against piston scuffing, ring sticking, and corrosion under severe marine conditions.

REXOIL OUTBOARD 2T meets the rigorous NMMA TC-W3 specification, ensuring excellent performance, engine cleanliness, and enhanced protection for water-cooled two-stroke outboard engines operating in fresh or saltwater environments. Suitable for pre-mix or oil injection systems at the manufacturer-recommended ratios, typically from 50:1 to 150:1.

Features and Benefits

- Completely ashless formulation prevents spark plug fouling, piston deposits, and reduces exhaust smoke for cleaner combustion and improved environmental performance.
- Prevents piston ring sticking and keeps combustion chambers clean, optimizing engine performance and reliability over prolonged usage.
- Contains specialized corrosion inhibitors to protect internal engine components against saltwater corrosion, even during storage periods.
- Reduced smoke emission formula minimizes impact on waterways and marine ecosystems.

Approval and Specifications

NMMA TC-W3; API TC

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	7,7 – 9,5
Density @ 15^{0}C g/ml	ASTM D4052	0,880 - 0,890
Viscosity Index	ASTM D2270	Min. 90
Flash Point, °C	ASTM D92	Min. 220
Pour Point, °C	ASTM D97	Max. -26

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr