SCOOTER 4T 10W-30

API SL, JASO MB

REXOIL SCOOTER 4T 10W-30 is a high-performance, premium quality multigrade engine oil, specially engineered to meet the demanding requirements of modern four-stroke scooters. Its advanced quality base oil formulation, combined with carefully selected additives, provides outstanding wear protection, superior cleanliness, and stable performance across a wide range of temperatures.

The product is optimized for scooters equipped with **Continuously Variable Transmissions (CVTs)** and **dry clutch mechanisms,** ensuring smooth power delivery, enhanced acceleration, and improved fuel economy. By meeting **API SL** and **JASO MB** standards, **REXOIL SCOOTER 4T 10W-30** is perfectly suited for urban riders who face frequent stop-and-go traffic, high ambient temperatures, and variable road conditions.

This lubricant not only extends engine life but also offers a comfortable and reliable riding experience by reducing vibration, controlling deposits, and maintaining excellent lubrication even under high stress.

Features and Benefits

- Fuel Efficiency: JASO MB friction modifiers reduce internal friction, providing improved fuel economy and smoother acceleration.
- Engine Cleanliness: Keeps pistons, valves, and combustion chambers cleaner for longer service life.
- Oxidation Stability: Prevents oil thickening and viscosity breakdown at high operating temperatures.
- Cold Start Protection: Excellent low-temperature fluidity ensures fast oil circulation at start-up.
- Urban Reliability: Designed to handle frequent starts, stops, and high-load urban traffic conditions.

Approval and Specifications

API SL; JASO MB

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	10,3 – 12,3
Density @ 15^{0}C g/ml	ASTM D4052	0,855 - 0,875
Viscosity Index	ASTM D2270	Min. 140
Flash Point, °C	ASTM D92	Min. 220
Pour Point, °C	ASTM D97	Max. -32
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,0

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr