MOTORCYCLE 4T 15W-50

API SL, JASO MA2

REXOIL MOTORCYCLE 4T 15W-50 is a premium quality 4-stroke engine oil developed to meet the rigorous demands of modern motorcycles. Formulated with 100% virgin base oils and a carefully engineered additive package, it delivers exceptional wear protection, enhanced cleanliness, and stable viscosity across wide temperature ranges.
Its optimized frictional properties ensure outstanding wet-clutch performance and reliable power transfer, making it the ideal choice for both city traffic and long-distance touring.

It is recommended for use in all modern 4-stroke motorcycles that require **SAE 15W-50** and **API SL** performance, including both air-cooled and liquid-cooled engines, and is fully compatible with wet-clutch systems in compliance with **JASO MA2** standards.

Features and Benefits

- **Durable Protection –** Strong oil film protects engine parts even under high RPM and heavy load.
- **Smooth Clutch & Gears –** Optimized friction ensures easy gear shifting and prevents clutch slippage.
- Heat Resistance – Excellent thermal stability prevents oil thickening and harmful deposits.
- **Engine Cleanliness –** Keeps pistons, valves, and combustion chambers free from sludge and dirt.
- **Cold Start Safety –** Fast oil circulation reduces wear during ignition in low temperatures.
- **Longer Engine Life –** Reduces friction and wear, ensuring durable and consistent performance.

Approval and Specifications

API SL; JASO MA2

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	17,0 – 20,5
Density @ 15^0C g/ml	ASTM D4052	0,870 - 0,890
Viscosity Index	ASTM D2270	Min. 135
Flash Point, °C	ASTM D92	Min. 230
Pour Point, °C	ASTM D97	Max. -30
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,2

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr