SCOOTER 4T 20W-40

API SL, JASO MB

REXOIL SCOOTER 4T 20W-40 is a specially developed premium multigrade lubricant designed to meet the unique demands of modern four-stroke scooters. Utilizing a high-quality mineral-based formulation combined with carefully selected performance additives, this lubricant ensures optimal protection and smooth operation under frequent urban driving conditions. Meeting API SL and JASO MB standards, it specifically addresses scooter engine needs by offering superior wear protection, cleanliness, and optimal friction characteristics suitable for scooters equipped with continuously variable transmissions (CVTs) and dry clutch mechanisms.

It is ideal for everyday riding conditions characterized by frequent starts and stops, moderate to high ambient temperatures, and varying road conditions.

Features and Benefits

- JASO MB friction modifiers lower internal friction, resulting in noticeable fuel savings, improved throttle response, and smoother acceleration.
- Advanced oxidation inhibitors prevent oil thickening and viscosity loss at high operating temperatures, ensuring stable lubrication and reduced deposit formation.
- Ensures quick oil circulation upon start-up, protecting engine parts from premature wear during cold starts or after prolonged storage.
- Specially designed viscosity grade provides consistent lubrication, smooth acceleration, and reliable performance, even under frequent urban stop-and-go conditions.

Approval and Specifications

API SL; JASO MB

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	13,5 – 16,0
Density @ 15^{0}C g/ml	ASTM D4052	0,870 - 0,885
Viscosity Index	ASTM D2270	Min. 120
Flash Point, °C	ASTM D92	Min. 230
Pour Point, °C	ASTM D97	Max. -25
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,0

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr