MOTORCYCLE 4T 10W-40

API SL, JASO MA2

REXOIL MOTORCYCLE 4T 10W-40 is a semi-synthetic four-stroke engine oil formulated with high-quality virgin base oils and advanced additive systems to ensure reliable performance in modern motorcycles. Its optimized 10W-40 viscosity grade provides excellent lubrication during cold starts and maintains a strong oil film under high operating temperatures.

The product is designed to meet **API SL** and **JASO MA2** specifications, delivering outstanding engine cleanliness, wear protection, and thermal stability. It is suitable for use in a wide range of four-stroke motorcycle engines, including both air-cooled and liquid-cooled types, where **SAE 10W-40** grade oils are recommended.

Features and Benefits

- Reduces metal-to-metal contact and extends engine life under demanding riding conditions.
- Maintains consistent lubrication from cold start to high operating temperatures.
- Minimizes sludge and deposit build-up, keeping pistons and valves cleaner for longer service life.
- Protects against oil thickening and maintains performance during extended drain intervals.
- Resists breakdown at high RPMs and heavy traffic conditions, ensuring continuous protection.
- Reduces internal friction, contributing to smoother operation and improved efficiency.

Approval and Specifications

API SL; JASO MA2

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	13,0 - 16,2
Density @ 15^0C g/ml	ASTM D4052	0,860 - 0,885
Viscosity Index	ASTM D2270	Min. 145
Flash Point, °C	ASTM D92	Min. 210
Pour Point, °C	ASTM D97	Max. -33
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,0

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr