MOTORCYCLE 4T 20W-50

API SN, JASO MA2

REXOIL MOTORCYCLE 4T 20W-50 is a state-of-the-art 4-stroke engine oil, designed to meet the extreme demands of modern motorcycles. Blended with 100% virgin base oils and an advanced additive system, it ensures exceptional wear protection, superior thermal stability, and smooth clutch engagement. Its robust multi-grade formulation guarantees consistent performance in intense urban traffic, long-distance touring, and high-temperature conditions.

It is recommended for use in all modern 4-stroke motorcycles that require SAE 20W-50 and API SN performance, including both air-cooled and liquid-cooled engines, and is fully compatible with wet-clutch systems in compliance with JASO MA2 standards.

Features and Benefits

- **Maximum Engine Protection –** Creates a durable oil film that safeguards engine components even under severe load.
- **Optimized Clutch Performance –** Designed for smooth gear shifting and to prevent clutch slippage.
- **Outstanding Thermal & Oxidation Stability –** Protects against oil breakdown in high-temperature environments.
- **Superior Engine Cleanliness –** Keeps pistons, valves, and combustion chambers free from harmful deposits.
- **Reliable Cold Start Protection –** Ensures rapid lubrication during cold starts, reducing wear at ignition.
- **Extended Engine Life –** Reduces friction and wear, prolonging the performance of your motorcycle.

Approval and Specifications

API SN; JASO MA2

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	17,5 – 21,2
Density @ 15^0C g/ml	ASTM D4052	0,880 - 0,895
Viscosity Index	ASTM D2270	Min. 125
Flash Point, °C	ASTM D92	Min. 235
Pour Point, °C	ASTM D97	Max. -26
Total Base Number, mg KOH/g	ASTM D2896	Min. 8,0

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr