MOTORCYCLE 4T 10W-30

API SN, JASO MA2

REXOIL MOTORCYCLE 4T 10W-30 is a premium quality four-stroke motorcycle engine oil developed with high-purity base oils and advanced additive systems. It is specifically designed to provide stable lubrication, wear protection, and deposit control under a wide range of operating conditions.The formulation meets API SN and JASO MA2 requirements, ensuring compatibility with modern motorcycle engines equipped with wet clutches and integrated gearboxes. Its optimized frictional properties prevent clutch slippage while maintaining smooth power transfer. With a balanced viscosity profile (10W-30), the oil offers reliable cold-start performance as well as consistent film strength at high temperatures, supporting engine durability during extended use

This product is suitable for air-cooled and liquid-cooled four-stroke engines, making it a versatile choice for motorcycles, scooters, and similar applications requiring 10W-30 grade lubricants.

Features and Benefits

- Provides a strong lubricating film that reduces metal-to-metal contact and protects critical engine parts such as pistons, camshafts, and bearings.
- Meets JASO MA2 standards, ensuring smooth clutch operation without slippage or grabbing.
- Maintains stable viscosity and film strength under heavy loads, reducing gear wear, pitting, and scuffing.
- Advanced detergent-dispersant system minimizes deposits on pistons, rings, and valves, extending engine cleanliness and efficiency.
- Excellent low-temperature properties provide fast oil circulation at startup, reducing wear during the most critical lubrication phase.
- Excellent low-temperature properties provide fast oil circulation at startup, reducing wear during the most critical lubrication phase.

Approval and Specifications

API SN; JASO MA2

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	10,2 - 12,3
Density @ 15^0C g/ml	ASTM D4052	0,860 - 0,885
Viscosity Index	ASTM D2270	Min. 140
Flash Point, °C	ASTM D92	Min. 210
Pour Point, °C	ASTM D97	Max. -33
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,0

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr