MOTORCYCLE POWER 4T 5W-30

API SP, JASO MA2

REXOIL MOTORCYCLE POWER 4T 5W-30 is a **high-performance fully synthetic motorcycle engine oil**, specially formulated for the latest generation of 4-stroke motorcycles. With advanced synthetic base oils and modern additive technology, it ensures **optimum lubrication, excellent wear protection, and enhanced fuel efficiency** under all operating conditions.

Its lower viscosity grade is designed to **reduce internal friction** and improve engine response, while providing reliable shear stability to maintain consistent viscosity under high RPM and severe riding stress. The oil's excellent **thermal and oxidation resistance** prevents deposit formation and oil breakdown at high temperatures, ensuring a clean, efficient, and long-lasting engine performance.

REXOIL MOTORCYCLE POWER 4T 5W-30 is recommended for:

- **Modern High-Efficiency Motorcycles** – Designed for fuel economy and superior engine cleanliness.
- **Sports & Street Bikes** – Provides fast response and reliable lubrication at high RPM.
- **Touring & Commuter Motorcycles** – Ensures stability in long-distance and city traffic conditions.
- **Motorcycles with Integrated Gearboxes & Wet Clutches** – Meet JASO MA2 specification for smooth clutch performance and gear shifting without slippage.
- **All-Season Use** – Delivers excellent cold-start performance and stable lubrication in both hot and cold climates.

Features and Benefits

- Low-viscosity synthetic formulation reduces internal drag for better fuel economy.
- Maintains a protective oil film under severe stress and high engine speeds.
- Shear-resistant formulation keeps viscosity consistent under heavy loads.
- Longer drain intervals and sustained performance for reliable engine durability.
- Prevents sludge and deposits, keeping the engine clean and efficient.
- Rapid circulation reduces wear during ignition in low temperatures.

Approval and Specifications

API SP; JASO MA2

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	10,0 - 12,3
Density @ 15^{0}C g/ml	ASTM D4052	0,835 - 0,855
Viscosity Index	ASTM D2270	Min. 155
Flash Point, °C	ASTM D92	Min. 210
Pour Point, °C	ASTM D97	Max. -35
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,2

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr