MOTORCYCLE POWER 4T 0W-40

API SP, JASO MA2

REXOIL MOTORCYCLE POWER 4T 0W-40 is an ultra-high performance, fully synthetic engine oil specifically developed for the latest generation of 4-stroke motorcycles. Formulated with advanced synthetic base oils and cutting-edge additive technology, it ensures exceptional lubrication and protection under all operating conditions. The formulation is engineered to maximize power transfer by reducing internal friction, providing sharper throttle response and stronger acceleration. Its outstanding shear stability keeps viscosity consistent under severe riding stress, high RPM, and prolonged operation.

REXOIL MOTORCYCLE POWER 4T 0W-40 is recommended for a wide range of motorcycles and riding conditions:

- **High-Performance Sports Motorcycles –** Delivers optimum protection and fast response at high RPM.
- **Touring & Long-Distance Riding –** Maintains stable lubrication and oxidation resistance during continuous operation.
- **Urban Commuting –** Designed to handle frequent stop-and-go traffic, acceleration, and idling.
- **Off-Road & Adventure Bikes –** Protects against wear and deposits in dusty, hot, and challenging terrain.
- **Motorcycles with Integrated Gearboxes & Wet Clutches** – Meets JASO MA2 specification for smooth clutch engagement and gear shifting without slippage.

Features and Benefits

- Special friction-optimised formula ensures sharper throttle response and faster acceleration without compromising protection.
- Maintains consistent viscosity in high-revving engines and extreme riding conditions, preventing oil film collapse.
- Outstanding resistance against oxidation and deposits, keeping engines cleaner and preventing power loss at high temperatures.
- Longer drain intervals and sustained protection for riders who demand reliability on both short city rides and long touring journeys.
- Keeps pistons, rings, and valves free from harmful deposits, ensuring maximum combustion efficiency.

Approval and Specifications

API SP; JASO MA2

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	13,0 - 15,8
Density @ 15^0C g/ml	ASTM D4052	0,835 - 0,855
Viscosity Index	ASTM D2270	Min. 160
Flash Point, °C	ASTM D92	Min. 210
Pour Point, °C	ASTM D97	Max. -40
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,2

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr