MOTORCYCLE 4T 10W-50

API SN, JASO MA2

REXOIL MOTORCYCLE 4T 10W-50 is a premium quality, fully synthetic engine oil specially developed for modern four-stroke motorcycles. It is blended with 100% virgin base oils and advanced additive technology to provide maximum protection and consistent performance even under extreme riding conditions.

Formulated to meet **API SN** and **JASO MA2** specifications, it delivers outstanding engine cleanliness, superior wear protection, excellent thermal stability, and smooth clutch and gear operation. The **JASO MA2** classification ensures compatibility with wet clutch systems, preventing clutch slippage and providing precise power transfer.

REXOIL MOTORCYCLE 4T 10W-50 is recommended for:

- High-performance motorcycles used for both daily commuting and long-distance touring.
- Air- and liquid-cooled four-stroke engines requiring SAE 10W-50 viscosity grade.
- Motorcycles operating in high ambient temperatures, heavy traffic, or extended service intervals.
- Sport bikes, cruisers, and off-road motorcycles demanding reliable lubrication at high RPMs and heavy loads.

Features and Benefits

- **Wide Temperature Protection:** Excellent fluidity at low temperatures and high-film strength at extreme heat.
- **Wet Clutch Performance:** JASO MA2 approved for smooth gear shifting and anti-slip clutch operation.
- **Superior Wear Protection:** Extends engine life under severe operating conditions.
- **Thermal & Oxidation Stability:** Maintains performance, resists oil thickening and deposit formation.
- **Clean Engine Operation:** Keeps pistons, valves, and components free of sludge and varnish.

Approval and Specifications

API SN; JASO MA2

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	17,0 - 21,2
Density @ 15^{0}C g/ml	ASTM D4052	0,855 - 0,875
Viscosity Index	ASTM D2270	Min. 150
Flash Point, °C	ASTM D92	Min. 210
Pour Point, °C	ASTM D97	Max. -35
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,3

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr