GEAR BOXES PAO

ISO 220

REXOIL GEAR BOXES PAO ISO 220 is a premium fully synthetic industrial gear lubricant developed with **Polyalphaolefin (PAO) technology** for demanding gear and power transmission applications. Its advanced formulation is designed to maintain a strong lubricating film under **high loads, elevated temperatures and prolonged operating conditions**, providing dependable protection for critical gearbox components.

The high-viscosity PAO formulation offers excellent resistance to **thermal breakdown and oxidation**, helping maintain lubricant performance and equipment cleanliness over extended service periods. It is particularly suited to heavy-duty machinery where high load-carrying capacity, long oil life and reliable protection are essential.

REXOIL GEAR BOXES PAO ISO 220 is recommended for **heavy-duty enclosed gearboxes, industrial speed reducers, conveyors, mixers, crushers, mills, material-handling equipment and other power transmission systems** requiring an ISO VG 220 synthetic gear lubricant.

Features and Benefits

- **Advanced PAO synthetic technology** provides excellent lubricant stability and high-performance protection.
- **High viscosity and strong film strength** provide reliable separation of heavily loaded gear surfaces.
- **Excellent oxidation resistance** helps extend lubricant service life and maintain performance over prolonged operation.
- **Outstanding thermal stability** supports reliable lubrication at elevated operating temperatures.
- **High load-carrying performance** helps protect gears and bearings under demanding mechanical loads.
- **Effective anti-wear protection** helps reduce component surface damage and premature wear.
- **Excellent resistance to sludge and deposit formation** helps maintain a clean lubrication system.
- **Reliable rust and corrosion protection helps** protect internal gearbox components against environmental effects.
- **Low volatility** helps minimize lubricant loss during high-temperature operation.
- **Long service potential** can contribute to reduced maintenance frequency and lower operating costs.

Approval and Specifications

DIN 51517 Part 3; AGMA 9005-F16; ISO 12925 (L-CKC/L-CKD); ISO 6743-6 (L-CKC/L-CKD); ZF TE-ML 04F; ZF TE-ML 27; David Brown S1.53.101; AIST 224 (US Steel 224); Fives Cincinnati Machine Gear

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (40°C), [cSt]	ASTM D445	198,0 – 242,0
Viscosity Index	ASTM D2270	Min. 130
Density @ 15^0C g/ml	ASTM D4052	0,830 - 0,855
Flash Point, °C	ASTM D92	Min. 230
Pour Point, °C	ASTM D97	Max. -45

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr