GEAR BOXES PAO

ISO 460

REXOIL GEAR BOXES PAO ISO 460 is a premium fully synthetic industrial gear lubricant formulated with high-performance **Polyalphaolefin (PAO)** base oils and an advanced additive system. It provides excellent thermal and oxidative stability, high film strength and reliable protection against wear, scuffing, micropitting, rust and corrosion under heavy-load and demanding operating conditions.

Designed for **enclosed industrial gearboxes** requiring ISO VG 460 lubricants, it is suitable for spur, helical, bevel and planetary gears, as well as heavy-duty gear reducers and power transmission systems. It is ideal for demanding applications in **steel, cement, mining, paper, power generation, marine and general industrial equipment**, helping maintain clean operation, extend component life and support longer lubricant service intervals.

Features and Benefits

- **Fully Synthetic PAO Technology** – Provides superior performance and stability under demanding operating conditions.
- **Excellent Thermal & Oxidation Stability** – Resists lubricant degradation at elevated temperatures and supports extended service life.
- **Outstanding Load-Carrying Performance** – Provides strong protection under heavy loads, high torque and shock-load conditions.
- **Superior Wear & Scuffing Protection** – Helps protect gears and bearings against wear, scuffing and micropitting.
- **High Film Strength** – Maintains a durable lubricating film for reliable protection of heavily loaded gear surfaces.
- **Excellent Corrosion Protection** – Helps protect metal components against rust and corrosion.
- **Clean Gear Operation** – Resists sludge, varnish and deposit formation, supporting cleaner equipment.
- **Excellent Shear Stability** – Maintains consistent lubrication performance during demanding service.
- **Extended Equipment Life** – Helps reduce component wear and improve the reliability of industrial gear systems.

Approval and Specifications

DIN 51517 Part 3; AGMA 9005-F16; ISO 12925 (L-CKC/L-CKD); ISO 6743-6 (L-CKC/L-CKD); ZF TE-ML 27; David Brown S1.53.101; AIST 224 (US Steel 224); Fives Cincinnati Machine Gear

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (40°C), [cSt]	ASTM D445	414,0 – 506,0
Viscosity Index	ASTM D2270	Min. 135
Density @ 15^{0}C g/ml	ASTM D4052	0,835 - 0,855
Flash Point, °C	ASTM D92	Min. 240
Pour Point, °C	ASTM D97	Max. -35

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr