

NEON RUBBER GREASE

NLGI 3,5

REXOIL NEON RUBBER GREASE is a smooth-textured, water-resistant lubricating grease formulated with mineral base oils and calcium soap thickener. It offers good mechanical stability, strong resistance to water washout, and protection against rust and corrosion. Suitable for a wide range of industrial and automotive applications operating under moderate loads and temperatures. It is suitable for general industrial and automotive bearings, chassis lubrication, water pump and agricultural equipment lubrication, as well as marine and other water-exposed environments thanks to its good water resistance, and is recommended for moderate temperatures up to +70 °C

Features and Benefits

- High mechanical stability, resists softening and leakage during service.
- Strong adhesion to metal surfaces reduces leakage and consumption.
- Provides reliable lubrication under shock loads and vibration.
- Reduces wear and extends service life of components.
- Compatible with conventional sealing materials.
- Economical multipurpose grease for a wide variety of equipment.

Approval and Specifications

DIN 51502, KP3,5E-10, ISO 12924, ISO L-XBBFA-3,5

Technical Specifications

Test	Method	Typical Properties
NLGI		3,5
Soap Type		Calcium
Color		Green
Penetration, worked, 25°C, 0,1 mm	ASTM D217	205 - 220
Dropping Point, °C	ASTM D566	Min.95
Operating Temp. Range (°C)	-	- 10 to +70

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.