ANTIFREEZE TYPE D

REXOIL ANTIFREEZE TYPE D is a premium quality, mono ethylene glycol based, Organic Acid Technology (OAT) long-life coolant developed specifically to meet the requirements of Renault vehicles requiring RN Type D specification. It is formulated with advanced corrosion inhibitors free from silicates, phosphates, amines, nitrites, and borates, ensuring superior protection of aluminum engines and modern cooling system components.

This product is recommended for use in Renault passenger cars and light commercial vehicles requiring RN Type D coolant, as well as in aluminum and mixed-metal engine cooling systems, including radiators, heater cores, and water pumps.

Features and Benefits

- Provides excellent protection against freezing and overheating.
- Delivers long-term corrosion protection for aluminum and mixed-metal cooling system components.
- Prevents scale formation and deposits, ensuring efficient heat transfer.
- Protects against cavitation, extending water pump life.
- Silicate, phosphate, amine, nitrite, and borate free formulation.
- Extended service life, reducing maintenance intervals.
- Compatible with modern Renault cooling system requirements.
- Helps maintain optimal engine operating temperature under severe conditions.

Approval and Specifications

RENAULT RN TYPE D; MAN 324 Type SNF; MB Approval 325.3; VOLVO TRUCKS S TYPE D, 1286083/00; AFNOR NF R 15-601 Type 2; Renault/Nissan RNUR 4101001/S Type D; Renault Trucks 4101001/S Type D; CUMMINS 85T8-2, 90T8-4; DEUTZ/MWM 0199-2091; IVECO 18-1830-A002; JOHN DEERE H 24 B1 / C1, VW/Audi/Seat/Skoda TL 774F / TL 774D; Jaguar/ Land Rover STJLR 651.5003, BMW GS 94000; Opel/GM/Vauxhall GMW 3420; Aston Martin; Fiat/Lancia 9.55523; Mitsubishi MHI; MWM 0199-99-2091/11; Mack 014 GS 17009

Technical Specifications

Test	Method	Typical Properties
Color	-	Yellow
Boiling Point, °C	ASTM D 1120	Min. 105
Freezing Point, °C	ASTM D 1177	Min. 25
Density @ 20ºC, kg/l	ASTM D 4052	1,045 – 1,100
pH	ASTM D 1293	7,5 – 10,0

Health and Safety

This product does not pose a significant health or safety risk when used appropriately. For detailed safety information, please refer to the Safety Data Sheet (SDS).

Storage & Handling

Store in a cool, dry, and well-ventilated area, away from direct sunlight and moisture. Keep containers tightly closed to prevent contamination. Dispose of contents and containers in accordance with local regulations.

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.
Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78
www.rexoil.com.tr